

TOUCH
DRY
IN TWO HOURS

SOLVENT
FREE

CAN BE LAID ON
DAMP
SURFACES

USE STRAIGHT
OUT OF
THE TIN

NO
JOINS

GREAT FOR
COMPLEX
SHAPED
AREAS

SELF-
LEVELLING
FOR A GREAT FINISH

TriRoof

HPX

HYBRID POLYMER ROOFING SYSTEM

GUARANTEE
10 YEAR
SINGLE LAYER*

GUARANTEE
20 YEAR
DOUBLE LAYER*



Product Description

Premium roofing system that repairs, restores, waterproofs and protects.

- Adheres to most substrates incl. asphalt, felt, rubber, concrete, most metals, roofs and flooring**
- Ideal for roofs, balconies, terraces and wet rooms
- Exceptionally flexible (up to 300 times its normal size)

Other Uses

- Wet rooms
- Wet areas (under-tile) in bathrooms, kitchens, balconies, auxiliary rooms, etc.
- Available in light and dark grey

20 & 10 YEAR GUARANTEE*

- Tack-free time: 2-4 hrs
- Full cure time: 8-16 hrs
- Fibre free formula

Why use the TriRoof HPX System?

- Can be applied to damp surfaces
- One coat application, easy to use
- Solvent-free, non-flammable
- Suitable for working temperatures of +5°C to +35°C
- Temperature resistant (once cured) -20°C to +80°C
- Breathable until cured, allowing moisture to evaporate
- Contains stain reducing properties

*20 Year Guarantee

Repair any leaks with HPX and TriRoof CSM 450gm Bandage consolidated. Then apply 1 Layer of HPX (1.6kg – 1.8kg per sqm depending on substrate) with TriRoof 225g CSM consolidated followed up with a 1kg -1.2kg sqm final coat after first layer has dried.

*10 Year Guarantee

Repair any leaks with HPX and TriRoof CSM 450gm Bandage consolidated then 1 layer of HPX (1.6kg – 1.8kg sqm depending on substrate).

**Adheres to most surfaces. Testing is advised prior to install. All contaminants must be removed prior to install.

Tricel Composites (GB)

Unit A Fox Way, Atkinson Street,
Leeds LS10 1PS, UK
Tel: +44 113 270 3133

Tricel Composites (NI)

Milltown Industrial Estate, Greenan Rd,
Warrenpoint, Newry BT34 3FN, UK
Tel: +44 28 4175 3738

www.triroof.co.uk