



HPX

STEP-BY-STEP PHOTO REPAIR GUIDE



1 SWEEP AREA CLEAN

Sweep any excess water off the area with a stiff brush. Sweep any dirt, dust and debris off the area with stiff brush.



2 POUR HPX ONTO AREA

Open up the HPX Foil pack bag (cut the corner of the foil bag off) and pour HPX onto the area.



3 USE BANDAGE ROLL & CONSOLIDATE

If there are any splits on the roof use 450 gsm 75mm bandage roll. You must also consolidate the fibres using a paddle roller.



4 USE LAMBSWOOL ROLLER

Using a lambswool roller and painter pole, apply the HPX to the entire area, ensuring an adequate amount of liquid is applied to ensure the substrate is fully encapsulated.



5 POUR FURTHER HPX ONTO AREA

Pour further HPX onto the substrate, repeating the above process to ensure the substrate is fully encapsulated.

6 PHOTOS OF FINAL FINISH



Tricel Composites (GB)
Unit A Fox Way, Atkinson Street,
Leeds LS10 1PS, UK
Tel: +44 113 270 3133

Tricel Composites (NI)
Milltown Industrial Estate, Greenan Rd,
Warrenpoint, Newry BT34 3FN, UK
Tel: +44 28 4175 3738

www.triroof.co.uk